



# NTK BEARING PRECISION AXLE CORP.



6304VVNRC3 Bearing 2D drawings and 3D CAD models

## NSK 6304VVNRC3 Single Row Ball Bearings

Bearing No. 6304VVNRC3

|                                 |   |
|---------------------------------|---|
| Category                        | Single Row Ball Bearings  |
| Inventory                       | 0.0   |
| Manufacturer Name               | NSK   |
| Minimum Buy Quantity            | N/A   |
| Weight                          | 0.15  |
| EAN                             | 0029176580475   |
| Product Group                   | B00308  |
| Enclosure                       | 2 Seals   |
| Precision Class                 | ABEC 1   ISO P0   |
| Maximum Capacity / Filling Slot | No  |
| Rolling Element                 | Ball Bearing  |
| Snap Ring                       | Yes   |
| Internal Special Features       | No  |
| Cage Material                   | Steel   |
| Enclosure Type                  | Non-Contact Seal  |
| Internal Clearance              | C3-Loose  |
| Inch - Metric                   | Metric  |
| Long Description                | 20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C3-Loose Internal Clearance; Steel Cage; |
| Other Features                  | Deep Groove   Rubber Seal   With Snap Ring  |
| Category                        | Single Row Ball Bearing   |



## NTK BEARING PRECISION AXLE CORP.

|                          |   |
|--------------------------|---|
| UNSPSC                   | 31171504  |
| Harmonized Tariff Code   | 8482.10.50.68   |
| Noun                     | Bearing   |
| Keyword String           | Ball  |
| Manufacturer URL         | <a href="http://www.nskamericas.com">http://www.nskamericas.com</a> |
| Manufacturer Item Number | 6304VVNRC3  |
| Weight / LBS             | 0.3197  |
| d                        | 0.787 Inch   20 Millimeter  |
| Inner Race Width         | 0 Inch   0 Millimeter   |
| D                        | 2.047 Inch   52 Millimeter  |
| Outer Race Width         | 0.591 Inch   15 Millimeter  |